



## EM537 three phase energy meter-65A-Modbus- Multi-rates

- CE approved
- Three phase metering 5 din modules
- Direct metering up to 65A
- 128×64 Lattice LCD display
- Clear blue backlight display
- 50 pulse output
- Modbus RTU with 16 bit CRC
- 1,2,3 and 4 tariff meter option
- Accuracy class B according to EN50470-3
- Accuracy class 1 according to IEC62053-21
- Memory back-up (EEPROM)



### Characteristics

Type of measurement	Volts (L1,L2,L3-N) Amps (L1,L2,L3,Σ,Neutral) kW&kvar&kVA&PF (L1,L2,L3,Σ) Frequency kWh,kvarh (+, -, Σ) kW&kvar Demand (+, -, Σ) Tariff kWh& kvarh (T1,T2,T3,T4,Σ)
Rated current	5A
Rated voltage	3*133/230---3*277/480V
Frequency (Hz)	50 or 60Hz
Maximum current	65A
Maximum value measured	999999.99kWh,999999.99kvarh
Power consumption	<2W 10VA
Current terminals flexible 1×mm <sup>2</sup>	0-10mm <sup>2</sup>
RS485 cable	AWG18
another terminal flexible 1×mm <sup>2</sup>	0-2.5mm <sup>2</sup>
<b>Time of Use</b>	
Rates	0~4
Separate Import & Export Registers	585
Programmable special days	64
Time-keeping accuracy	<0.5S/day
Power off clock running time	>5 years
<b>Modbus serial comms</b>	
Protocol	Modbus RTU with 16 bit CRC
Baud Rate(bps)	1200,2400,4800,9600(default)
Bus loading(pcs)	< 64

<b>General data</b>	
Pulse width(ms)	80
Pulse constant(imp/kWh)	1000
LED constant(imp/kWh)	1000
<b>Dimension</b>	
Width (mm)	90
Height (mm)	104.5
Depth (mm)	60
<b>Environmental</b>	
Operating temperature	-25°C - +55°C
Storage temperature	-40°C - +70°C